

# NLV2101

2D CMOS imager

RS232

 **USB (HID/VCP)**

### + Related products



#### M5

- Stationary device
- 2D CMOS imager
- RS232, Keyboard Wedge, USB (HID/VCP)
- IP 52, ABS, up to 50 fps



#### NLV2001

- Stationary device
- Barcode laser scanner
- RS232, Keyboard Wedge, USB (HID/VCP)
- IP 67, Metal



#### OPI4002

- Wireless device
- 2D CMOS imager
- IEEE 802.15.4
- Equipped with powerjack



## Operating indicators

- Visual: 1 LED (red/green/orange)
- Non-visual: Buzzer

## Communication

- RS232: DB9 PTF connector with external power supply
- USB: Ver. 1.1, HID/VCP, USB-A connector

## Power

- Voltage requirement: 5V ± 10%
- Current consumption: Max. 330mA

## 2D Imager Optics

- Light source: Illumination 4 red LEDs 630 nm, aiming 2 green LEDs 527 nm
- Scan method: CMOS area sensor, SXGA (1.3 million pixels), gray scale
- Scan rate: Up to 30 fps
- Trigger mode: Manual, multiple read, auto-trigger, serial software trigger
- Image format: Windows Bitmap, JPEG, TIFF
- Gradulation: 256, 16, 2
- Image output mode: 4 resolutions (full, 1/2, 1/3, 1/4), 2 ranges (horizontal, vertical)
- Curvature: R>15 mm (EAN8), R>20 mm (EAN13)
- Min. resolution at PCS 0.9: 0.127 mm / 5 mil, \*0.169 mm / 7 mil\*, at Code39 / PDF417 and \*Data Matrix\*
- Min. PCS value: 0.45
- Field of view: Horizontal 47°, Vertical 37.5°
- Depth of field: At PCS 0.9 \*PDF417\* and Code 39  
\*52 - 202 mm / 2.05 - 7.95 in (1.0 mm / 39 mil)\*,  
\*97 - 122 mm / 3.82 - 4.80 in (0.5 mm / 20 mil)\*,  
52 - 232 mm / 2.05 - 9.13 in (0.25 mm / 10 mil),  
67 - 162 mm / 2.64 - 6.38 in (0.15 mm / 6 mil),  
97 - 122 mm / 3.82 - 4.80 in (0.127 mm / 5 mil)

## Supported Symbolologies

- Barcode (1D): JAN/UPC/EAN incl. add on, Codabar/NW-7, Code 11, Code 39, Code 93, Code 128, GS1-128 (EAN-128), GS1 DataBar (RSS), IATA, Industrial 2of5, Interleaved 2of5, ISBN-ISSN-ISMN, Matrix 2of5, MSI/Plessey, S-Code, Telepen, Tri-Optic, UK/Plessey
- Postal code: Chinese Post, Korean Postal Authority code
- 2D code: Aztec Code, Aztec Runes, Codablock F, Composite codes, Data Matrix (ECC200/ECO-140), Maxi Code (mode 2~5), MicroPDF417, Micro QR Code, PDF417, QR code

## Durability

- Temperature in operation: 0 to 45 °C / 32 to 113 °F
- Temperature in storage: -20 to 60 °C / -4 to 140 °F
- Humidity in operation: 20 - 85% (non-condensing)
- Humidity in storage: 20 - 90% (non-condensing)
- Ambient light immunity: Fluorescent 10,000 lx max, Direct sun 100,000 lx max, Incandescent 10,000 lx max
- Antistatic electricity: 15kV (non-destructive)
- Drop test: 0.75 m / 2.5 ft drop onto concrete surface
- Protection rate: IP 67

## Physical

- Dimensions (w x h x d):  
46 x 58 x 24.5 mm / 1.81 x 2.28 x 0.96 in
- Weight body: Ca. 120 g / 4.2 oz (excl. cable)
- Case: Metal, Black

## Regulatory & Safety

- Product compliance: CE, FCC, VCCI, RoHS

## Sold separately

- Power supply 100-240V/0.5A, 50/60 Hz, 5V/2A (for RS232)

## Models

- Interface versions: RS232, USB

Copyright Opticon. All rights reserved. This information is subject to change without prior notice. For availability, contact your local representative.

- **The Netherlands:** Hoofddorp  
- **France:** Issy Les Moulineaux  
- **Germany:** Dietzenbach  
- **Italy:** Castel Maggiore (BO)  
- **Spain:** Valencia  
- **Sweden:** Järfälla  
- **United Kingdom:** Luton, Bedfordshire  
- **U.S.A.:** Renton, WA  
- **Japan:** Warabi City

- **Taiwan:** Taipei  
- **P.R.China:** Shanghai  
- **Australia:** Kariang  
- **Brazil:** São Paulo

Opticon Sensors Europe B.V  
European headquarters  
Opaalaan 35  
2132 XV Hoofddorp  
The Netherlands  
phone: +31 (0)23-5692700  
fax: +31 (0)23-5638266  
email: sales@opticon.com  
internet: www.opticon.com

**OPTICON**  
WWW.OPTICON.COM



## About BarcodesInc

### Who We Are

BarcodesInc is North America's leading provider of... [unreadable text]

### We Owe Our Success To You

Our success is due to the support of our customers... [unreadable text]

## Why Choose BarcodesInc?

### Dedicated Account A UbU Yf

Our Account Managers will not compromise when it comes to providing you top-notch service. Your Account Manager is the primary point of contact for your business and makes it a priority to get to know you, your company and all your needs.

### Highly-Trained Technical Support

Our technical staff has the broadest knowledge and every significant certification in the industry. One of our friendly experts is always available to suggest products and solutions for any situation.

### Incredible Value

Our purchasing power means big savings for you. Whatever your project, our team will work hard to deliver a solution that fits your budget.

### Largest Inventory in the Industry and Same-Day Shipping

Whatever your barcoding, mobile computing, or printing needs, we will fill your order and ship it the same day.

### Premier Access to Top Manufacturers

BarcodesInc maintains strong strategic partnerships with the leading manufacturers in barcoding, mobile computing, printing and RFID.

### Responsive Customer Service

Every phone call and email is responded to promptly, completely and accurately by our customer service team.

### Easy Returns

Damaged, defective or incorrectly ordered goods may be returned without hassle.

## BRANDS



AND MORE