



Symbol LS3578-ER

Rugged, cordless scanner with integrated Bluetooth



FEATURES

Wide working range:

4 in. (10 cm) to 45 ft. (13.7 m)

Allows workers to scan items at varying distances without having to move, reducing fatigue and speeding task completion

Integrated Bluetooth

Class 2 v1.2 (Serial Port and HID Profiles with authentication and security)

Cordless scanning with secure wireless data transmission

Cordless scanning

Enables real-time bar code data collection unrestricted by a cable, reducing repairs from cable failure

Rugged design withstands multiple 6.5-ft. (2-m) drops to concrete

Ensures maximum reliability with less downtime resulting from accidental drops

Scan bar codes over a wide range of distances

The Symbol LS3578-ER rugged, cordless scanner provides the greatest working range of any available rugged scanner, allowing employees to scan items from as close as 4 inches/10 cm to as far away as 45 feet/13.7 m. It also allows employees to quickly switch from reading bar codes on inventory to capturing smaller symbologies on bar code menus and pick lists.

In the yard, warehouse, distribution center, manufacturing plant or retail store, the Symbol LS3578-ER offers superior performance and reliability as well as a user-friendly form factor that helps ensure comfortable use over long shifts. Plus, integrated Bluetooth provides reliable and secure wireless data transmission between the scanner and host, including Motorola's rugged VC5090 Vehicle-Fixed Mount Mobile Computer.

Cordless freedom for improved productivity

With no cord between the scanner and host, employees can move freely throughout their work environment, increasing productivity and efficiency while keeping supply chain inventory up to date at all times. Plus, having no cord reduces downtime from cable breakdowns – a common point of failure in handheld devices used in industrial facilities.

Rugged design to maximize uptime

As rugged as it is innovative, the Symbol LS3578-ER is designed for scan-intensive industrial applications in the harshest operating conditions. Industry-leading impact tests ensure reliable performance in spite of the inevitable accidental drops. The device is impervious to dust and water, and its exit window is scratch-resistant and recessed for the highest level of durability. As a result, you avoid unnecessary equipment downtime or expensive equipment replacement costs.

Low total cost of ownership (TCO)

In addition to enhancing productivity, the Symbol LS3578-ER offers a low TCO. The industrial-strength construction maximizes the scanner's working life, and multiple on-board interfaces provide true plug-and-play simplicity with your host system today and tomorrow. Support for Remote Scanner Management (RSM) enables you to discover, provision and upgrade devices from a central remote location, dramatically reducing management time and costs.

And since even the most rugged devices require a support plan, a full complement of Enterprise Mobility Services are available to help you protect your investment and maintain peak performance.

For more information, contact us at +1.800.722.6234 or +1.631.738.2400, or visit us at www.symbol.com/ls3578er

SPECIFICATION SHEET

SYMBOL LS3578-ER

IP65-rated seal (electronic enclosure)

Protects against water and dust for reliable performance in the harshest environments

Bright LED and beeper with adjustable volume

Helps ensure that decode feedback is clearly visible and audible to users, even in noisy environments

Multi-point communication

Use up to three scanners with a single cradle, reducing capital expenditures and maintenance costs

Bright 650 nm laser aiming dot

Delivers clearly visible line for more accurate scanning

Advanced data formatting

Eliminates costly modifications to the host software

Batch mode operation

Increases application design flexibility to better meet your specific needs

Remote scanner management ready

Enables you to discover, provision and upgrade devices from a central remote location, reducing management time and costs

Symbol LS3578-ER Specifications

Physical Characteristics	
Dimensions:	7.34 in. L x 4.82 in. W x 2.93 in. D (18.65 cm H x 12.25 cm W x 7.43 cm D)
Weight: (including LiON battery)	14.8 oz. (420 gm)
Battery:	2200 mAh Lithium Ion Battery
Battery charge time:	Fully charged (100%) in 3 hours
Color:	Twilight Black and Yellow
Performance Characteristics	
Scanner type:	Retrocollective
Light source:	650 nm visible laser diode
Scan repetition:	36 scans per second typical
Minimum element width:	7.5 mil (0.191 mm)
Nominal working distance:	4 in to 45 ft (10cm to 13.7m)
Print contrast:	25% minimum reflective difference
Roll (Tilt) ¹ :	+/- 10 degrees from normal
Pitch ² :	+/- 65 degrees from normal
Skew (Yaw) ³ :	+/- 60 degrees from normal
Decode capability:	UPC.EAN, UPC.EAN with Supplemental, UCC.EAN 128, JAN 8 & 13, Code 39, Code 39 Full ASCII, Code 39 Trioptic, Code 128, Code 128 Full ASCII, Codabar (NW7), Interleaved 2 of 5, Discrete 2 of 5, Code 93, MSI, Code 11, Code 32, Bookland EAN, IATA, UCC/EAN RSS and RSS variants
Interfaces supported:	RS232, Keyboard Wedge, Wand Emulation, Scanner Emulation, IBM 468X/469X, USB and Synapse
User Environment	
Operating temperature:	-4° to 122°F (-20° to 50°C)
Storage temperature:	-40° to 140°F (-40° to 60°C)
Humidity:	5% to 95% relative humidity, noncondensing
Sealing:	Sealed to IP65 specifications
Drop specifications:	Unit functions normally after repeated 6.5-ft. 2-m) drops to concrete
# of Cradle Insertions:	250,000+ insertions
Ambient light immunity:	Immune to direct exposure of normal office and factory lighting conditions, as well as direct exposure to sunlight.
Electrostatic discharge:	Conforms to 15 kV air discharge and 8 kV of contact discharge

Cradles	STB 3508 and FLB 3508	STB 3578 and FLB 3578
Power requirements:	4.75 – 14 VDC	4.75 – 14 VDC
Typical current draw:		
Not charging	10 mA	105 mA @5V 45 mA @9V
Fast rate charge	915 mA @5V 660 mA @9V	915 mA @5V 660 mA @9V
Slow rate charge	480 mA @5V 345 mA @9V	480 mA @5V 345 mA @9V

Radio specification

Radio:	Bluetooth, Class 2, Version 1.2, Serial port and HID Profiles 2.402 to 2.480 GHz adaptive frequency hopping (co-existence with 802.11 wireless networks) Data rate: 720 kbps
--------	--

Regulatory

Input transient protection:	IEC 1000-4-(2,3,4,5,6,11)
EMI/RFI:	FCC Part 15 Class B, ICES-003 Class B, European Union EMC Directive, Japan VCCI/MITI/Dentori
Laser safety:	IEC825-1 Class 2

Warranty

The Symbol LS3578-ER is warranted against defects in workmanship and materials for a period of 3 years (36 months) from date of shipment, provided that the product remains unmodified and is operated under normal and proper conditions. See full warranty for details.

Recommended Service

Service from the Start - Bronze



MOTOROLA

motorola.com

Part number SS-LS3578-ER. Printed in USA 05/07. MOTOROLA and the Stylized M Logo and SYMBOL and the Stylized SYMBOL Logo are registered in the US Patent & Trademark Office. All other product or service names are the property of their respective owners. ©2007 Motorola, Inc. All rights reserved. For system, product or services availability and specific information within your country, please contact your local Motorola office or Business Partner. Specifications are subject to change without notice.