


VP2160




Folds down to only 6.5cm

The Nexa NP-2160 All in One terminal packs great features, versatility and value into a sleek and neat design. It enhances the atmosphere of any business while providing excellent performance and reliability.



Adding to the NP-2160's premium feature set, it uses the world's leading touch screen technology, Projected Capacitive, (PCAP). Where many Pos Terminals use a resistive touch overlay that is subject to physical wear or accidental damage, PCAP touch has no overlay, so these potential points of failure are removed, giving greater length of life and reliability.









Panel

LCD Size 15"

Resolution 1024 x 768 Luminance 250 cd/m²

Touch Screen 10-points Multi Touch P-CAP

System

CPU Fanless Intel J1900 2.42GHz Quad Core

Memory 4GB SO-DIMM DDR3L 1067/1333MHz , upgradeable to 8GB

Hard Disk Drive 64GB 2.5" SATA SSD

I/O

USB 4x USB2.0 port, USB 3.0 x1

COM RS-232 x 3, DB-9 Pin9 with RI/5V/12V selectable by BIOS.

COM 1: RS-232, RJ-50 with convert to DB-9 cable COM 2: RS-232, RJ-50 with convert to DB-9 cable

COM 3: RS-232/422/485, DB-9

COM 6: RS-232, Internal reserved for 2x20 VFD Customer Display

Ethernet 1x Gigabit LAN VGA 1x 2nd VGA port

Cash Drawer 1x RJ-11 port 12V / 24V DC

Physical

Dimensions 36 x 28.9 x 25.2 cm (14.2 x 11.4 x 9.9 inch)

Weight 5 kg, 11 lb

Mounting 75mm x 75mm VESA wall mount, (not suitable for pole mount).

Operating Temperatures $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Storage Temperature $-20^{\circ}\text{C} \sim 60^{\circ}\text{C}$

Operating Humidity 20% to 85% RH (non condensing)

Accessories MSR, VFD, 10" Customer Facing LCD

