



## TD-4420T Series

203dpi Direct Thermal Printers

TD-4420TN  
TD-4420TNP  
TD-4420TNC



Healthcare,  
medical and  
laboratory



Warehousing  
and logistics



Retail

# Thermal Transfer Printers

4-inch 203dpi Barcode Label and Receipt Printers

TD-4420TN  
TD-4420TNP  
TD-4420TNC



Introducing the next era of four-inch desktop thermal printers from Brother. These precision built barcode label and receipt printers, deliver performance, quality, and integration at an exceptional value. From inventory and shipping to barcode and shelf labelling – now you can easily and affordably produce the labels you need, with the reliability and support that only Brother delivers.



## Effortless integration

Experience improved operational efficiency with seamless integration into existing and future workflows utilising Bpac, Software Development Kits (SDK's), PDF Crop tool, BarTender and the support of a variety of printer command systems, including ZPLII emulation



## Reliable technology

Thermal technology is made up of less moving parts delivering greater reliability for your business



## Warranty

Delivering peace of mind with a 12 month return to base warranty on hardware and a 6 month return to base warranty of print heads. Rapid exchange is also available as an optional add-on

## Technical Specifications for the TD-4420T Series

	TD-4420TN	TD-4420TNP	TD-4420TNC
<b>Tear Bar</b>	Yes	N/A	N/A
<b>Peeler (PA-LP-001)</b>	No (available as an option)	Yes (installed)	No
<b>Cutter (PA-CU-001)</b>	No (available as an option)	No	Yes (installed)
<b>Printing</b>			
<b>Print Technology</b>	Thermal Transfer		
<b>Print Resolution</b>	203dpi		
<b>Print Speed</b>	MAX 152.4mm/sec (6 ips) (Under Brother standard environment)		
<b>Print Width (MAX)</b>	108mm (4.25 inch)		
<b>Print Length (MAX)</b>	25,400mm (1000 inch)		
<b>Print Length (MIN)</b>	5mm (0.09 inch)		
<b>Media Sensor Type</b>	Gap (Transmissive), Black mark (Reflective)		
<b>Media Sensor Location</b>	Reflective (adjustable), Gap (fixed)		
<b>Release Mode</b>	Standard: Continuous, tear off	Peeler	Cutter
<b>Size</b>			
<b>Weight</b>	Printer: 2.50kg	Printer & Peeler: 2.68kg	Printer & Cutter: 2.87kg
<b>Dimensions</b>	204mm (W) (8.03 inch) 177.5mm (H) (6.99 inch) 280mm (D) (11.02 inch)	204mm (W) (8.03 inch) 177.5mm (H) (6.99 inch) 322mm (D) (12.68 inch)	204mm (W) (8.03 inch) 177.5mm (H) (6.99 inch) 333mm (D) (13.11 inch)
<b>Control Panel</b>	1 LED with 3 colours 1 button (Feed)		
<b>Interface</b>			
<b>USB</b>	Standard: USB Ver.2.0 (Full Speed) (Type B)		
<b>Serial</b>	Standard: RS232C (DB9 male)		
<b>Wired LAN</b>	Standard: 10/100BASE-TX		
<b>USB Host Port</b>	Standard: USB Type-A   Class ID: HID, USB mass-storage device class   USB Regulation: 2.0		
<b>Bluetooth</b>	Not supported		
<b>BluetoothProfile</b>	-		
<b>WLAN</b>	Not supported		
<b>WLAN Mode</b>	-		
<b>WLAN Security</b>	-		
<b>Memory</b>			
<b>RAM</b>	64MB SDRAM		
<b>Flash</b>	128MB NAND-FLASH   User area   SDRAM: 2048 KB   Flash: 80640 KB		
<b>Power Supply</b>			
<b>Adapter</b>	AC adapter Input: AC 100-240V, 2.0A, 50-60Hz   Output: DC24V, 2.5A, 60W, LPS		
<b>Media Specification</b>			
<b>Types</b>	Continuous, die-cut, black mark, fan-fold, notch		
<b>Wound Type</b>	Outside wound		
<b>Media Width</b>	20 ~ 112mm (0.79 inch to 4.41 inch) catalogue described spec		
<b>Media Length</b>	5mm ~ Max. print length (0.20inch to Max inch) Tear mode : 50mm ~ Max. print length   Peeler mode: 25.4 ~ 152.4mm   Cutter mode: 25.4mm ~ Max. print length		
<b>Thickness</b>	0.06 ~ 0.19 mm		
<b>Diameter (Max)</b>	5inch OD (around 74~75M long)		
<b>Core Diameter (Min)</b>	25.4mm & 38.1mm (1.0 inch & 1.5 inch)		
<b>Ribbon specification</b>			
<b>Types</b>	Premium Wax, Resin, Semi (Wax/Resin)		
<b>Wound Type</b>	Outside wound		
<b>Ribbon Width</b>	40 ~ 110mm (1.57 inch to 4.33 inch)		
<b>Suggested Paper Core Width</b>	0.5 inch paper core: fixed width 110mm with 2 notches in each side 1 inch paper core: fixed width 110mm with 2 notches in each side 1 inch paper core: paper core width is the same as ribbon width and use with ribbon spindles		
<b>Inner Paper Core &amp; Ribbon Length</b>	0.5 inch paper core: Max. OD 40mm, 110M long   1 inch paper core: Max. OD 67mm, 300M long		

Software	
Label Editing Software	BarTender Ultra Lite Edition
Windows Printer Driver	Windows 10 and Server 2016 Windows 8.1 and Server 2012 R2 Windows 8 and Server 2012 Windows 7 and Server 2008 R2 Windows Server 2008
MAC Printer Driver	macOS 10.14.x macOS 10.13.x macOS 10.12.x OS X 10.11.x OS X 10.10.x
Linux Printer Driver	Ubuntu V11.04-16.04 Fedora 24 SUSE Linux Enterprise Server 12 CentOS Linux 7.2 Red Hat Enterprise 7.3
Setting Tool	BPM (Brother Printer Management Tool) Support OS Windows 7 Windows 8, 8.1 Windows 10
Mobile SDK	Not supported
Mobile Transfer Express Mobile Deploy	Not supported
Windows SDK	Windows 10 and Server 2016 Windows 8.1 and Server 2012 R2 Windows 8 and Server 2012 Windows 7 and Server 2008 R2 Windows Server 2008
Supported Command	FBPL-EZD (EPL,ZPL,ZPL2,DPL)
SAP Device Type	SAP_BASIS Release 6.20~7.11, except 7.10.
Development Support Tool	CommTool (Brother Communication Tool)
Bar Code Symbologies	<b>Linear:</b> Code128UCC, Code128 subsets ABC, EAN128, Interleaved 2 of 5, Interleaved 2 of 5 with check digit, Code39, Code39 with check digit, Code93, EAN13, EAN8, UPCA, UPCE, EAN and UPC 2 (5) digits add-on, Codabar, Postnet, MSI, MSI with check digit, PLESSEY, China post, ITF14, Code11, TELEPEN, TELEPENN, PLANET, Code49, Deutsche Post Identcode, Deutsche Post Leitcode, LOGMARS <b>2-dimensional:</b> GS1 DataBar, GS1 DataMatrix, Maxicode, AZTEC, PDF417, QR Code, Micro PDF 417
Fonts	8 alpha-numeric bitmap fonts for FBPL Monotype Image® true type font engine with one CG Triumvirate Bold Condensed scalable font
Operating Characteristics	
Operating Temperature	Operate: 5 ~ 40°C
Operating Humidity	25~85% non-condensing
Storage Temperature	40 ~ 60 °C
Storage Humidity	10~90% non-condensing
Printer Safety	EMC / RMC
Warranty	
Hardware	12 Month Return to Base
Print Head	6 Month or 30kms Return to Base
Options	Rapid Exchange - contact Brother at <a href="mailto:info@brother.com.au">info@brother.com.au</a> for more information
Package Contents	
Package Contents	Printer, AC Adapter, Power Cord, USB Cable, Documents
	Printer, Label Peeler, AC Adapter, Power Cord, USB Cable, Documents
	Printer, Cutter, AC Adapter, Power Cord, USB Cable, Documents

## Brother International Australia

Suite 1, Level 3, Building A,  
11 Talavera Road, Macquarie Park, NSW, 2113  
Phone: 02 9887 4344

[brother.com.au](http://brother.com.au)



[youtube.com/user/BrotherAU/videos](https://youtube.com/user/BrotherAU/videos)



[linkedin.com/company/brother-international-australia/](https://linkedin.com/company/brother-international-australia/)



[facebook.com/BrotherAustralia/](https://facebook.com/BrotherAustralia/)

**brother**  
at your side

All specifications correct at the time of printing and are subject to change. Brother is a registered trademark of Brother Industries Ltd. Brand product names are registered trademarks or trademarks of their respective companies.