



# Direct Thermal Desktop Printers

4-inch 203dpi Barcode  
Label and Receipt Printers

**TD-4420DN**  
**TD-4420DNP**  
**TD-4420DNC**



Introducing the next era of four-inch desktop thermal printers from Brother. These precision built barcode label and receipt printers, deliver performance, quality, and integration at an exceptional value. From inventory and shipping to barcode and shelf labelling – now you can easily and affordably produce the labels you need, with the reliability and support that only Brother delivers.



## Effortless integration

Experience improved operational efficiency with seamless integration into existing and future workflows utilising Bpac, Software Development Kits (SDK's), PDF Crop tool, BarTender and the support of a variety of printer command systems, including ZPLII emulation



## Reliable technology

Thermal technology is made up of less moving parts delivering greater reliability for your business



## A full thermal print solution

Design and print from start to finish with Brother's free P-touch Editor label design software. With hundreds of templates and barcode creation, label development for any industry can be achieved



## Warranty

Delivering peace of mind with a 12 month return to base warranty on hardware and a 6 month return to base warranty on print heads. Rapid exchange is also available as an optional add-on

## Technical Specifications for the TD-4420D Series

	TD-4420DN	TD-4420DNP	TD-4420DNC
<b>Tear Bar</b>	Yes	N/A	N/A
<b>Peeler (PA-LP-001)</b>	No (available as an option)	Yes (installed)	No
<b>Cutter (PA-CU-001)</b>	No (available as an option)	No	Yes (installed)
<b>Printing</b>			
<b>Print Technology</b>	Direct Thermal		
<b>Print Resolution</b>	203 dpi		
<b>Print Speed</b>	MAX 203.2mm/sec (8 ips) (Under Brother standard environment)		
<b>Print Width (MAX)</b>	108.4mm (4.27 inch)		
<b>Print Length (MAX)</b>	3,000mm (118.11 inch)		
<b>Media Sensor Type</b>	Gap (Transmissive), Black mark (Reflective)		
<b>Media Sensor Location</b>	Reflective (adjustable), Gap (fixed)		
<b>Release Mode</b>	Standard: Continuous, tear off	Peeler	Cutter
<b>Size</b>			
<b>Weight</b>	Printer: 2.08kg	Printer & Peeler: 2.20kg	Printer & Cutter: 2.45kg
<b>Dimensions</b>	180mm (W) (7.08 inch) 155mm (H) (6.10 inch) 224mm (D) (8.82 inch)	180mm (W) (7.08 inch) 155mm (H) (6.10 inch) 259mm (D) (10.20 inch)	180mm (W) (7.08 inch) 155mm (H) (6.10 inch) 267mm (D) (10.51 inch)
<b>Control Panel</b>	3 LED 3 button (Power/ Feed/ Print)		
<b>Interface</b>			
<b>USB</b>	Yes: USB Ver.2.0 (Full Speed) (Type B)		
<b>Serial</b>	Yes: RS232C (DB9 male)		
<b>Wired LAN</b>	10/100BASE-TX		
<b>Bluetooth</b>	Not supported		
<b>WLAN</b>	Not supported		
<b>Memory</b>			
<b>RAM</b>	256MB		
<b>Flash</b>	64MB (User area 40MB)		
<b>Power Supply</b>			
<b>Adapter</b>	AC adapter (100 - 240 V 50/60Hz)		
<b>Media Specification</b>			
<b>Types</b>	Wristbands, Continuous, Die Cut, Fan Fold, Perforated, Tag		
<b>Wound Type</b>	Outside wound		
<b>Media Width</b>	19 ~ 118mm (0.75 inch to 4.65 inch) catalogue described spec		
<b>Media Length</b>	6.4mm ~ Max. print length (0.25 inch to Max inch)   Tear mode: 18mm ~ Max. print length Peeler mode: 17 ~ Max. print length   Cutter mode: 20mm ~ Max. print length		
<b>Thickness</b>	0.06 ~ 0.279mm		
<b>Diameter (Max)</b>	127mm		
<b>Core Diameter (Min)</b>	12.7mm		

Software	
Label Editing Software	P-touch Editor ver. 5.2 and supports BarTender Lite as optional
Windows Printer Driver	Microsoft Windows7 (x86/x64), Microsoft Windows8 (x86/x64), Microsoft Windows 8.1 (x86,x64), Microsoft Windows10 (x86,x64), Microsoft Windows Server 2008 (x86,x64), Microsoft Windows Server 2008 R2 (x64), Microsoft Windows Server 2012 (x64)/Server 2012R2 (x64)Microsoft Windows Server 2016
MAC Printer Driver	macOS 10.14.x, macOS 10.13.x, macOS 10.12.x, OS X 10.11.x, OS X 10.10.x
Linux Printer Driver	Ubuntu V11.04-16.04 Fedora 24 SUSE Linux Enterprise Server 12 CentOS Linux 7.2 Red Hat Enterprise 7.3
Setting Tool	BPM (Brother Printer Management Tool) Support OS Windows 7 Windows 8, 8.1 Windows 10
Mobile SDK	Android 4.0.3 or later, iOS 8 or later
Mobile Transfer Express Mobile Deploy	Not supported
Windows SDK	Windows 10 and Server 2016, Windows 8.1 and Server 2012 R2, Windows 8 and Server 2012, Windows 7 and Server 2008 R2, Windows Server 2008
Supported Command	Raster, ESC/P, P-touch Template, ZPLII, CPCL (CPCL page print mode / CPCL line print mode)
SAP Device Type	SAP_BASIS Release 6.20~7.11, except 7.10.
Development Support Tool	CommTool (Brother Communication Tool)
Bar Code Symbologies	<b>Linear:</b> Code128UCC, Code128 subsets ABC, EAN128, Interleaved 2 of 5, Interleaved 2 of 5 with check digit, Code39, Code39 with check digit, Code93, EAN13, EAN8, UPCA, UPCE, EAN and UPC 2 (5) digits add-on, Codabar, Postnet, MSI, MSI with check digit, PLESSEY, China post, ITF14, Code11, TELEPEN, TELEPENN, PLANET, Code49, Deutsche Post Identcode, Deutsche Post Leitcode, LOGMARS <b>2-dimensional:</b> GS1 DataBar, GS1 DataMatrix, Maxicode, AZTEC, PDF417, QR Code, Micro PDF 417
Fonts	8 alpha-numeric bitmap fonts for FBPL Monotype Image® true type font engine with one CG Triumvirate Bold Condensed scalable font
Add-in for Microsoft	Microsoft Word 2007 (x86), Microsoft Word 2010 (x86), Microsoft Word 2013 (x86), Microsoft Word 2016 (x86), Microsoft Excel 2007 (x86), Microsoft Excel 2010 (x86), Microsoft Excel 2013 (x86), Microsoft Excel 2016 (x86), Microsoft Outlook 2007 (x86), Microsoft Outlook 2010 (x86), Microsoft Outlook 2013 (x86), Microsoft Outlook 2016 (x86)
Database File Compatibility	csv, txt, mdb, xls, accdb, xlsm, Microsoft SQL Server Database, accdb, xlsx, xlsx
Operating Characteristics	
Operating Temperature	Operate: 5 ~ 40°C
Operating Humidity	25 ~ 85% non-condensing
Storage Temperature	40 ~ 60 °C
Storage Humidity	10 ~ 90% non-condensing
Printer Safety	EMC / RMC
Warranty	
Hardware	12 Month Return to Base
Print Head	6 Month or 30kms Return to Base (whichever is first)
Options	Rapid Exchange - contact Brother at info@brother.com.au for more information
Package Contents	
Package Contents	Printer, AC Adapter, Power Cord, USB Cable, Documents
	Printer, Label Peeler, AC Adapter, Power Cord, USB Cable, Documents
	Printer, Cutter, AC Adapter, Power Cord, USB Cable, Documents

## Brother International Australia

Suite 1, Level 3, Building A,  
11 Talavera Road, Macquarie Park, NSW, 2113  
Phone: 02 9887 4344

[brother.com.au](http://brother.com.au)



[youtube.com/user/BrotherAU/videos](https://youtube.com/user/BrotherAU/videos)



[linkedin.com/company/brother-international-australia/](https://linkedin.com/company/brother-international-australia/)



[facebook.com/BrotherAustralia/](https://facebook.com/BrotherAustralia/)

**brother**  
at your side

All specifications correct at the time of printing and are subject to change. Brother is a registered trademark of Brother Industries Ltd. Brand product names are registered trademarks or trademarks of their respective companies.