

Backup BRICs LCD Series

BR650ELCD/850ELCD

BRD0012AU-02

Wall-Mountable UPS to Make the Most of Your Work Space

CyberPower®
Reliability. Quality. Value.



The BRICs LCD Series UPS offers home and small office users clean and stable battery backup while the featured RJ11/RJ45 port ensures phone, fax, and modem lines are protected from surges. With Automatic Voltage Regulation (AVR) stabilizes the AC signal and maintains a safe voltage, this allows the UPS to maintain safe power levels for the connected equipment without resorting to battery power. The multifunction LCD readout provides immediate access to precise information of critical power/battery condition. For convenient mounting, these units can be installed in either a horizontal or wall-mounted placement to make the most of your space.

The included PowerPanel® Personal Edition management software showcases the feature rich abilities such as input/output power voltage readings, self-diagnostics, and approximate battery backup time. With the Energy-Saving Technology, the BRICs Series UPS can save up to 75% of electricity therefore save your electricity expenses.

Applications

- Home and Home Office
- Home Theater System
- Small Office

Series Features

- GreenPower UPS™ Technology
- Automatic Voltage Regulator (AVR)
- EMI, RFI, Surge and Spike Protection
- Phone/Fax/Modem/DSL/Network Protection
- Auto-Restart/Auto-Charge
- LCD Status Monitor
- USB & Serial Connectivity Ports
- User-Replaceable Batteries
- Horizontal / Wall-mounted Use
- Cable Collector Included
- PowerPanel® Personal Edition Software

Energy-Saving

AVR

Surge Protection

Phone Line Protection

LCD Display

USB & Serial



GreenPower UPS™

ENERGY-SAVING TECHNOLOGY

The patented advanced energy-saving technology improves the operating efficiency and eliminates waste energy consumption.

Cable Collector



PowerPanel® Personal Edition Management S/W



AUTO-SHUTDOWN SOFTWARE

CyberPower PowerPanel® Personal Edition Management Software, is compatible with Windows7, Vista, XP, 2000 Pro., ME, 98, Windows Server 2008, 2003, Mac and Linux.

**Software functions may vary due to firmware version and/or hardware constraints.*

Backup BRICs LCD Series

BR650ELCD/850ELCD

CyberPower®
Reliability. Quality. Value.

Technical Specification

Model	BR650ELCD	BR850ELCD
Configuration		
Capacity (VA / Watts)	650/ 390	850 / 510
Energy-Saving Technology	Yes	
Input		
Frequency Range	47 Hz - 63 Hz (Auto Sensing)	
Output		
UPS Outlets (Numbers)	(6) Schuko or (6) FR or (6)UK (UK x 4+ IEC x 2) outlets	
On Battery Output Voltage	Simulated Sinewave at 230 Vac +/- 10%	
On Battery Output Frequency	50 Hz / 60 Hz +/- 1%	
Transfer Time (Typical)	4ms	
Overload Protection	On Utility: Circuit Breaker & Internal Current Limiting On Battery: Internal Current Limiting	
AVR	Yes	
Surge Protection and Filtering		
Surge Protection	Yes	
DSL / Phone / FAX / Modem Protection	Yes	
Physical		
Dimensions (H x W x D) (mm)	113.6 x 271 x 160.7	
Weight (kg)	4.4	
Battery		
Sealed Maintenance Free Lead Acid Battery	12V / 7AH x 1	12V / 8.5AH x 1
User Replaceable	Yes	
Typical Recharge Time	8 Hours	
Runtimes		
Half-load / Full-load (mins)	8 / 1	
Status Indicators		
Indicators	Power On	
Audible Alarms	On Battery, Low Battery, Overload	
Communication		
PowerPanel® Personal Edition	Windows 7 / Vista / XP / 2000, Server 2008 / 2003, Linux	
Management		
Self Test	Yes	
Auto-Charge / Auto-Restart	Yes	
Connectivity Ports	USB	

#All specifications are subject to change without notice. ©2012 Cyber Power Systems. All Trademarks are the property of their owners.

Packaging Content:



Product Unit



USB Cable



Phone Cable



Cable Collector



User Manual



Software CD



AVR
AUTOMATIC VOLTAGE REGULATOR

ENERGY-SAVING
TECHNOLOGY



DISTRIBUTED BY:

CyberPower's
Manufacturing
Facilities are
ISO 9001:2008,
ISO 14000, and
QC080000
Approved