

Specifications	SRP-350III	
Printing Method	Thermal Line Dot method	
Print Speed	Max. 250 mm/sec	
Print Resolution	180 dpi (7 dot/mm)	
Paper Size	80mm width, ?83mm	
Column Capacity	Font A: 42 Columns	
	Font B: 56 Columns	
Character Size	Font A:	1.25 x 3 mm (12 x 24 dots)
	Font B:	0.88 x 3 mm (9 X 24 dots)
Character Set	Alpha Numeric Character: 95	
	Extended Character 128 x 37 pages	
	International Characters: 32	
Emulation	ESC/POS TM	
Drivers	Windows, OPOS, JPOS, Linux CUPS (Linux Kernel 2.4.18 and later), Mac Driver	
Bar-code type	1D: UPC-A/E, JAN-13/8, ITF, Code 39, Code 128, CODABAR, Code 93	
	2D: PDF417, QR Code	
Memory	64Mbit SDRAM, 32 Mbit FlashROM	
Data Buffer	4 Kb	
NV Bitmap Memory	256 Kb	
Interface	Serial	RS-232C
	Unidirectional Parallel	IEEE 1284
Drawer Kick-out	2 drawers through 1 RJ12 Connector	
Operating Temperature	0 ~ 45 ?C	
Power	24 DCV +/- 7%, 2.5A, External power supply	
External Dimensions (WxDxH)	145 x 203 x 146 mm	
Reliability	Head	150Km
	Mechanism	70,000,000 Lines
	Auto Cutter	1.8 Million Cuts
Safety Standards	UL, C-UL, FCC Class A, TUV-GS, CE Marking	