

## Key Features

- Optical effects (OFX) technology
- Intuitive, color LED scan adviser
- Compact, low-profile footprint
- Improved serviceability, flexibility
- Sensormatic® and Checkpoint® EAS deactivation options
- Indestructible buttons
- Six-sided scanning

## Why NCR?

With over 125 years of retail experience, NCR is a leading global provider of assisted- and self-service solutions. We help our clients around the world improve their customer interactions, implement change quickly and proactively, and transform their businesses to become leaders and change agents. We can help you, too.

## Technical Specifications

### SCAN PATTERN

- Laser Diode: 650nm
- Scan lines: 54
- Sides read: all sides
- Scan lines per second: 6300
- Scan line inches per second: 23,858" (60,600cm)

### SCALE CAPACITY

- 30lb in 0.01lb increments  
(15kg in 0.005kg increments)

### ADDITIONAL FEATURES

- POS interfaces: RS232, USB (NCR/PC and IBM), IBM RS485
- Auxiliary ports: 2 x RS232, 1 x PC-USB (Type-A)
- Vertical window: hurricane glass
- Horizontal top plate: EverScan or Sapphire
- Scan adviser clearly conveys scanner status
- Audio volume and pitch adjustment

### SYMBOLOLOGIES

- UPC/EAN with 2-digit and 5-digit add-on symbols
- Code 128
- Code 39 (3 of 9)
- Interleaved 2 of 5
- Codabar
- Italian Pharmacode
- GS1 DataBar™ (RSS): DataBar Omnidirectional, Stacked Omnidirectional, Expanded, Expanded Stacked
- GTIN and 2005 Sunrise Compliant

### SENSORMATIC ULTRA•MAX DEACTIVATOR 5274 EAS

- ZBAMB5274A coil set, 0352-0400-01 installation kit

### POWER

- 12V terminal power option via cable selection
- 90-264 VAC/47-63Hz
- 7 watts while scanning, 3 watts on standby

### ENVIRONMENTAL SPECIFICATIONS

- Working temperature: 32°F–104°F (0°C–40°C)
- Relative humidity: 5%–95% non-condensing

### PHYSICAL CHARACTERISTICS

- Compact scanner (W x L x D): 11.5" x 13.9" x 4" (29.2cm x 35.3cm x 10.2cm)
- Midsize scanner/scale (including third-party scale) (W x L x D): 11.5" x 15.7" x 4" (29.2cm x 39.9cm x 10.2cm)
- Long (W x L x D): 11.5" (+12" option) x 20" x 4" (29.2cm x 50.8cm x 10.2cm)

### COMPLIANT STANDARDS

- EU RoHS, CA RoHS, China RoHS, WEEE +1



Experience a new world of interaction

NCR RealPOS Low-Profile Bi-Optic Scanner/Scale

NCR continually improves products as new technologies and components become available. NCR, therefore, reserves the right to change specifications without prior notice.

All features, functions and operations described herein may not be marketed by NCR in all parts of the world. Consult your NCR representative or NCR office for the latest information.

NCR RealPOS is either a registered trademark or trademark of NCR Corporation in the United States and/or other countries. All brand and product names appearing in this document are trademarks, registered trademarks or service marks of their respective holders.

© 2008 NCR Corporation Patents Pending

EB5796-0908

www.ncr.com