

High Performance In-Counter Scanner and Scanner/Scale

The Magellan 8400 bi-optic scanner is the highest performance 5-sided POS scanner available today. The 8400 improves operational efficiency by achieving outstanding first-pass read rates, and represents the next step in value and checkout productivity from the Magellan family and Datalogic, breaking previous records of performance, reliability and value.

The 8400 can be configured as either scanner or scanner/scale combination with Datalogic's exclusive, patented All-Weighs® scale platter to ensure accurate produce and bulk food weighing at the checkout. Two remote scale display options are available; a single display on a pole and a dual display on a single pole for applications requiring separate displays for the cashier and customer. Magellan 8400 models are available in three lengths: long, medium, and short (scanner only) to accommodate various POS configurations.

FirstStrike® advanced software decoding algorithms provide the industry's best scanning speed and simultaneously

improve first pass read rates of damaged, wrinkled, or poorly printed bar codes delivering improved operational efficiencies at the retail checkout.

Flash memory allows for easy software upgrades that help extend the life of the retailer's investment. In addition, an auxiliary RS-232 port can be utilized in a variety of ways, including adding a handheld scanner, programming and configuring the scanner, or accessing the scanners label data output. For applications requiring electronic article surveillance (EAS), the 8400 can be equipped with Checkpoint EAS and can support aftermarket integrated Sensormatic EAS antennas with good read acknowledgement via the auxiliary RS-232 port. Optional Value Added Features provide optional information tools that help decrease front-end costs by managing information on scanner software and diagnostics.

Features

- Aggressive and ergonomic 360° 5-sided scanning for best in class scanning performance
- Renowned Magellan brand quality and reliability
- All-Weighs Scale Platter with integrated
 Produce Lift Bar or Produce Rail™ (Optional)
- FirstStrike advanced decoding software delivers the best performance in reading poor quality labels
- Flash memory for easy software upgrades in the field
- Multiple interface solution supports all popular host interfaces
- Powered auxiliary RS-232 port for easy integration of a handheld scanner
- Supports GS1 DataBar™ codes
- Checkpoint Systems and Sensormatic EAS compatible (Optional)
- Optional Value Added Features:
 - Host Download Lowers Service Cost and Improves Operations
 - Diagnostic Reporting For improved preventative maintenance
 - Productivity Index Reporting™ Helps identify poorly printed labels
 - Cashier Training™/ Ergonomic Index -Identifies Poor Scanning Habits
- Compatible with Mettler, Bizerba and other adaptive scales



www.scanning.datalogic.com

COLONIA TACO

Specifications

DECODING CAPABILITY

1D / LINEAR CODES Autodiscriminates all standard 1D codes including GS1 Databar™

linear codes

STACKED CODES GS1 DataBar Expanded Stacked; GS1 DataBar Stacked; GS1 DataBar

Stacked Omnidirectional

ELECTRICAL

AC Input: 100-250 VAC, 50-60 Hz AC POWER REQUIREMENTS

Power Consumption: Operating (Maximum): 8 Watts

Operating (Nominal): 7 Watts Sleep Mode: 4 Watts

ENVIRONMENTAL

ESD PROTECTION (AIR DISCHARGE) HUMIDITY (NON-CONDENSING)

TEMPERATURE

Operating: 10 to 40 °C / 50 to 104 °F

Storage/Transport: -40 to 70 °C / -40 to 158 °F

INTERFACES IBM 46xx; Keyboard Wedge: Scanner Only; OEM (IBM) USB; RS-232;

USB: Scanner Only

AUXILIARY PORTS EAS Port: Powered RS-232; Remote Scale Display; Scale Host

OPTIONAL FEATURES

ALL-WEIGHS SCALE PLATTER Integrated Produce Lift Bar; Produce Rail™

EAS FEATURES Checkpoint Systems: Integrated EAS hardware will work with

Counterpoint IV, V, VI and VII models Sensormatic: Good Read Acknowledgement

VALUE ADDED FEATURES Cashier Training™; Diagnostic Reporting; Host Download;

Productivity Index Reporting™ (PIR)

PHYSICAL CHARACTERISTICS

DIMENSIONS Depth (Below Counter): 10.2 cm / 4.0 in

Height (Above Counter): 13.0 cm / 5.1 in Length: Model 8401 (Short, Scanner Only): 35.6 cm / 14.0 in Model 8402 (Medium, Scanner Only): 40.1 cm / 15.8 in Model 8403 (Long, Scanner Only): 50.8 cm / 20.0 in

Model 8404 (Medium, Scanner/Scale): 40.1 cm / 15.8 in Model 8405 (Long, Scanner/Scale): 50.8 cm / 20.0 in

Width: 29.2 cm / 11.5 in SCALE CAPACITIES

Adjustments Required: Calibration Only

Capacity: 15.0 kg / 30.0 lb

Maximum Static Weight: 68.0 kg / 150.0 lb Minimum Increment: 0.005 kg / 0.010 lb

Vibration Immunity: 4 Programmable Filter Settings

READING PERFORMANCE

MOTOR SPEED 6,000 rpm READ HEIGHT 15.2 cm / 6.0 in READ RATE (MAXIMUM) 5,200 lines/sec.

READING INDICATORS Beeper (Adjustable Tone and Volume); Good Read LED

SCAN LINES SCAN ZONE 360° SIDES READ 5 Sides

SAFETY & REGULATORY

AGENCY APPROVALS The product meets necessary safety and regulatory approvals for its

intended use.

The Quick Reference Guide for this product can be referred to for a

complete list of certifications.

ENVIRONMENTAL COMPLIANCE Complies to EU RoHS

LASER CLASSIFICATION Caution Laser Radiation - Do not stare into beam; CDRH Class IIa; EN

60825 Class 1; IEC 60825 Class 1

UTILITIES

OPOS / JAVAPOS JavaPOS Utilities are available for download at no charge

OPOS Utilities are available for download at no charge

WARRANTY 1-Year Factory Warranty

the transfer of the state of the state

Datalogic S.p.A. in many countries and the Datalogic logo is a trademark of Datalogic

First Strike, All Weighs and Magellan are registered trademarks of Datalogic Scanning Inc. and Cashier Training, OmegaTek, Produce Rail and Productivity Index Reporting are trademarks of Datalogic Scanning Inc.

Other brand and product names may be trademarks of their respective owners.

www.scanning.datalogic.com