# LG FULL HD SIGNAGE MONITOR SE3KB SERIES



# **43SE3KB**















# **FEATURES:**

- 43" IPS Panel with Slim Design
- Wi-Fi Compatible and SNMP Support
- USB Cloning
- Ideal for Offices, Restaurants and Retail

- Native Resolution : 1920 x 1080 (Full HD)

Aspect Ratio : 16:9
Brightness : 350cd/m²
Contrast Ratio : 1,100:1

Orientation: Portrait and Landscape
Viewing Angle (H x V): 178° x 178°



\*LED LCD Monitors combine LCD screen with LED back light technology

# **Technical Data**

# 43SE3KB



Screen Size Panel Technology Aspect Ratio Native Resolution Brightness Contrast Ratio Dynamic CR Operating Hours Viiewing Angle (H x V) Orientation Surface Treatment

#### CONNECTIVITY

Input (Rear) Analogue Audio **External Control** USB Wi-Fi SD Card Wired LAN

Output (Rear) Digital Audio **External Control** 

#### PHYSICAL SPECIFICATIONS

Bezel Width Monitor Dimension (W x H x D) Dimension with optional stand (W x H x D) Carton Dimensions (W x H x D) Weight (head) Weight(head+stand) Packed Weight VESA™ Standard Mount Interface

## SPECIAL FEATURES

Additional

## **ENVIRONMENT CONDITIONS**

Operation Temperature Operation Humidity

### **POWER**

Power Supply DPM Typical / Smart Energy Saving on Power Off Power Type

### STANDARD (CERTIFICATION)

Safety **FMC** ErP/US EPA

### MEDIA PLAYER COMPATIBILITY

External Media player Attachable

### SOFTWARE COMPATIBILITY

SuperSign-w lite / SuperSign-c

#### **ACCESSORIES**

Included

Optional

43" (108cm) **IPS** 

16:9

1920 x 1080 (Full HD)

350cd/m<sup>2</sup> 1,100 : 1 (Native) 500,000:1 18 Hours / Day 178° x 178°

Portrait and Landscape

Hard coating(3H), Anti-glare treatment (Haze 1%)

HDMI(1), DVI-D(1), Support HDCP **RGB (1)** Yes (1) RS232C (1), IR receiver (1) Yes (2, USB2.0)

Dongle Compatible

Yes (1) RS232C (1)

RJ45 (1)

11.9mm(T/R/L), 18mm(B) 970mm x 564mm x 54mm 970mm x 622mm x 193mm 1052mm x 650mm x 123mm 10.0kg 12.3kg 12.6kg 200 x 200 mm

Temperature Sensor, Auto Config/Phase, SNMP Support, Input Label, Contents Scheduling, DPM Select, Holiday Schedule, Smart Energy Saving, File Play with USB, USB Cloning Built-in Speakers (10W x 2), PM Mode, Tile Mode, Lock Mode

0 °C to 40 °C 10 % to 80 %

100-240V~, 50/60Hz 0.7W 60W/45W 0.5W Built-In-Power

UL/cUL/CB/TUV/KC FCC Class "A"/CE/KCC, C-tick Yes / Yes (Energy Star 6.0)

Yes (MP500/MP700)

Yes / Yes (Via Software Download)

Remote Controller (include 2ea battery), QSG, Power Cable, RGB Cable, Regulation Book, Phono to RS232C Gender, IR Receiver

Stand (ST-432T), Wall bracket (LSW230B), VESA Adapter (AM-B220S), Media Player, Wi-Fi Dongle Kit (AN-WF500)

3 Years (Parts & Labour)

Warranty Disclaimer: All product specifications correct at time of printing. Specifications may change without prior notice.

