











**Enhanced performance Impact Receipt Printer** 

**SRP-275II** 

BIXOLON SRP-275II is more powerful and enhanced performance impact receipt printer to address customers' needs in restaurant, hospitality and retail industries. The fastest speed in its class(5.1 lps) allows kitchen orders to print faster than ever with two color, black and red printing to highlight special offers and print logos. Compact size with embedded power supply maximizes the efficiency of working environment. Eco-friendly design of the lowest standby power and various international standards provide reliability of the SRP-275II to the users.

### **HIGHLIGHTS**

- Fastest Print Speed up to 5.1 lps
- Eco-friendly design
- -Lowest Standby Power (0.91w)
- Compact Design
- -Embedded Power Supply
- Black Mark Sensor
- Fast USB Interface
- -USB 2.0 HS
- Large Capacity of Data Buffer
- -64KB Data Buffer
- -256KB NV Image

## **APPLICATIONS**

- -Retail
- -Hospitality
- -Healthcare
- -Banking
- -Parking

### **OTHER VALUE-ADDED FEATURES**

- Two color printing
- Easy to operate
- -Easy paper loading
- -Easy to install ribbon cartridge
- Proven reliability
- -18,000,000 MCBF
- -1,500,000 auto-cuts
- Bi-directional print
- · User friendly software tool
- -Logo download(NV image tool)
  -Code page selection(Virtual Memory Switch Manager)
- -Firmware download
- Two different type
- -SRP-275IIA(without Auto-cutter)
- -SRP-275IIC(with Auto-cutter)
- · Many valuable options
- -Splash Proof Cover(RSC 275)
- -External Buzzer(RBC-100)
- -BIXOLON Melodist(RMB-100)
- Various International Standards

# **BIXOLON SRP-275II SPECIFICATIONS**

PRINTING SPEED	
	Max 5.1 lps
PRINTING WIDTH	63.5mm(2.5 inch)
RESOLUTION	Horizontal: 80dpi
	Vertical: 144dpi
CHARACTER SIZE	Font A: 9 x 9, Font B: 7 x 9, Korean: 17 x 9, Chinese: 16 x 16
CHARACTERS PER LINE	Font A: 35 (3half dot: 33) , Font B: 40, Korean: 20, Chinese: 22 (3half dot: 21)
CHARACTER SET	Alphanumeric Character: 95
	Extended Graphics Pages: STD - 128 x 27, CHN - 128 x 21, KOR - 128 x 1
	International Character: 48
Sensor	Paper End, Black-mark, Paper Near End, Wall Mounting Paper Near End(option), Rear Cover Open
Printing Direction	Bi-direction
Receive Buffer	64Kbyte
NV Image	256Kbyte
CUTTER TYPE	A: Tear-bar
	C: Auto Cutter (Rotary)
WIDTH	76.0 ± 0.5mm
MAX. ROLL DIAMETER	83mm
SUPPLY METHOD	Easy Paper Loading
PRINTER UNIT (MCBF)	18,000,000 lines
HEAD	300,000,000 dots/wire
AUTO CUTTER	1,500,000 cuts
INK RIBBON COLOR RELIABILITY (CHARACTERS)	Black & Red
	Black: 1,500,000
	Red: 750,000
	Serial(RS-232C), Parallel(IEEE 1284), Ethernet, USB 2.0 HS
	Windows, OPOS, Linux, Virtual COM, Mac
	ESC/POSTM
	AC 100 ~ 240V / DC 24V, 1.5A
	160 x 239 x 157mm
	A: 2400g
PER)	C: 2500g
ARDS	FCC, UL, CE, CB, GS, GOST-R, CCC, KCC
JRE	0 ~ 40°C (32 ~ 104°F)
	Wall Mount Bracket(RWM - 350), Splash Proof Cover(RSC - 275), External Buzzer(RBC-100), BIXOLOI
-	CHARACTER SIZE CHARACTERS PER LINE CHARACTER SET  Sensor Printing Direction Receive Buffer NV Image CUTTER TYPE  WIDTH MAX. ROLL DIAMETER SUPPLY METHOD PRINTER UNIT (MCBF) HEAD AUTO CUTTER COLOR RELIABILITY (CHARACTERS)



Address 7-8th FL, Miraeasset Venture Tower, 685, Sampyeong-dong, Bundang-gu, Seongnam-si, Gyeonggi-do, 463-300, KOREA Tel +82 (0) 31 218 5500 Fax +82 (0) 31 218 5589 E-mail sales@bixolon.com