

## XT-2614Q

Specification	XT-2614Q
Processor	ARM Cortex-A7,4C, 1.0GHz
System Memory	1GB DDR3
Storage Device	8GB eMMC + Micro SD
Power Supply	12V/50W
OS Support	Android 4.4
Connectivity	
LAN Port	10/100/1000Mb x 1
Serial Port	2, DB9 x 2 ; 5V/12V support on COM2
UPS Port	N/A
Standard USB Port	3
OTG USB Port	1 x micro usb
Audio	Internal 2W speaker x 1
VGA Port	1
CR Port	N/A
LCD Besolution	14" TFT LCD 1366 x 768
Resolution	1366 x 768
Touch	True-flat PCAP touch with 10 point multi-touch support (IP65 on front panel)
Physical Dimension	
Dimension (W x D x H in mm)	271.2 x 371.6 x 252
Weight (N.W. in Kg)	Approx. 4 kg
Environment	
Operation Condition	0°C - 50°C, 20%RH - 90%RH
Storage Condition	-20°C - 70°C, 10%RH - 90%RH
Options	
SL-104	MSR Side Attachment
PD-2605UE	2 x 20 VFD, base-mount with 200mm pole, USB with Virtual COM support
PD-309UE	2 x 20 LCD, base-mount with 200mm pole, USB with Virtual COM support
PP-6901	3" thermal POS printer
WIFI	Internal WIFI 802.11b/g/n









Full Extended Mode

Low Profile Mode

Flat Folded Mode

- \* The product information and specifications are subject to change without prior notice.

Please refer to the web site for more attachment options.
SDK will be provided to integrate 2nd VGA function into POS application.

Design and Manufacturing in Taiwan by Posiflex Technology Inc.

The product information and specifications are subject to change without prior notice.

2015Q4



POSIFLEX TECHNOLOGY INC.

No. 6, Wuquan Rd., Wugu Dist., New Taipei City 24886, Taiwan

Tel: +886-2-2299-1599 E-mail: sales@posiflex.com.tw www.posiflex.com Fax: +886-2-2299-1819

Authorized Distributor / Reseller

Australian Distributor: Goodson Imports Pty Ltd, Representation in all main States and New Zealand, Head Office: 9 Liberty Road, Huntingwood NSW 2148, Sydney Australia

Ph: 02-8875 4544 Fax 02-8875 4588, www.goodson.com.au