

Disk Transponder WB-06



A X E Z E

RFID Access Control Products



Overview

The WB-06 Disk Transponder Wristband can be used with all Axeze LF readers, which currently include the KEP, KEN and KES ranges of Readers and Reader/Controllers. The strap is made from quality black leather

Specifications

| | |
|------------------------|---|
| Functionality | Read Only |
| Memory (bits) | 64 |
| Memory Pages | 1 |
| Operating Frequency | 134.2kHz |
| Modulation | FSK 134.2 kHz / 123.2 kHz |
| Transmission Principle | Half Duplex (HDX) |
| Power Source | Powered from the reader signal |
| Typical reading range | approx 11cm |
| Operating Temperature | -25° to +85°C |
| Storage Temperature | -40° to +100°C |
| Case Material | Poly-Oxy-Methylen (POM), black |
| Protection Class | IP 67 |
| EMC | Programmed code not affected by normal electromagnetic Interference or X-rays |
| Dimensions | φ29.4 mm ± 0.5 mm x 8.4 mm ± 0.4 mm |
| Weight | 8g |

Axeze Pty. Ltd. ABN 83 077 328 851
PO Box 387, Hindmarsh, South Australia 5007
+61 8 8340 8200 ph +61 8 8340 8211 fax sales@axeze.com.au www.axeze.com.au
The above specifications are subject to change without notice